



Main

| | |
|---------------------------|---------------------|
| Range of product | Series 56 |
| Range | Clipsal - 56 Series |
| Product brand | Clipsal |
| Product or component type | Socket-outlet |
| Device application | Power supply |
| Colour | Grey RAL 7035 |

Complementary

| | |
|-------------------------------------|--|
| Number of poles | 4 |
| Plug, socket category | Low voltage |
| Outlet standard | Australian/New Zealand |
| Plug, socket, control station shape | Straight |
| Number of modules | 3 |
| Number of power socket outlets | 1 protective cover |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 500 V AC 50 Hz |
| Poles description | 3P + E |
| Protection type | Without protection |
| Device mounting | Surface |
| Material | Polycarbonate for the cover |
| Contacts material | Phosphor bronze for the pins |
| Connections - terminals | Screw terminals 4...16 mm ² |
| Electrical connection | Industrial connector |
| Depth | 45 mm |
| Width | 101 mm |
| Height | 198 mm |
| Targeted country | Australia |

Environment

| | |
|---------------------------------------|-----------------------------|
| standards | AS/NZS 3123 AS/NZS 3133 |
| ambient air temperature for operation | -25...75 °C |
| IP degree of protection | IP66 conforming to AS 60529 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1650 - Schneider Electric declaration of conformity |
| REACH | Reference contains SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |